



Supo with nubs



The Supo N has a dimpled contact surface and is mainly installed on standing reinforcement. Installation is possible on reinforcement Ø 3-18 mm. To prevent twisting, the Supo N is mounted on a reinforcement crossing point. Thanks to the specially designed clamp shape, the Supo clamps optimally to the reinforcing steel. Quick installation is guaranteed. The dimples and the high-quality extruded fiber-reinforced concrete enable a very good exposed concrete surface. The concrete can also be supplied in other colors on request.



Supo with nubs

Article description	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22099000	Supo 15 N with studs, DBV-15-L1/F/T/A/D3-18	42	15	500 pieces/carton	2,800	15.000
22100000	Supo 20 N with studs, DBV-20-L1/F/T/A/D3-18	42	20	500 pieces/carton	3,200	12.000
22101000	Supo 25 N with studs, DBV-25-L1/F/T/A/D3-18	42	25	500 pieces/carton	3,400	11.000
22102000	Supo 30 N with studs, DBV-30-L1/F/T/A/D3-18	42	30	500 pieces/carton	3,800	10.000
22103000	Supo 35 N with studs, DBV-35-L1/F/T/A/D3-18	42	35	250 pieces/carton	5	8.000
22104000	Supo 40 N with studs, DBV-40-L1/F/T/A/D3-18	42	40	250 pieces/carton	6,800	7.500
22105000	Supo 45 N with studs, DBV-45-L1/F/T/A/D3-18	42	45	250 pieces/carton	8,500	7.000
22106000	Supo 50 N with studs, DBV-50-L1/F/T/A/D3-18	42	50	200 pieces/carton	11,100	6.600
22109100	Supo 55 N with studs, DBV-55-L1/F/T/A/D3-18	42	55	200 pieces/carton	11,600	5.600
22107000	Supo 60 N with studs, DBV-60-L1/F/T/A/D3-18	42	60	150 pieces/carton	12,500	5.100
22108000	Supo 65 N with studs, DBV-65-L1/F/T/A/D3-18	42	65	125 pieces/carton	13,300	4.500
22109000	Supo 70 N with studs, DBV-70-L1/F/T/A/D3-18	42	70	100 pieces/carton	14	4.000