


## Kapo with studs



The Kapo is mainly mounted on standing reinforcement. Installation is possible on reinforcement Ø 3-10 mm. To prevent twisting, the Kapo is mounted on a reinforcement crossing point. The spring steel clamp Ø 2 mm clamps the Kapo optimally to the reinforcing steel. Quick installation is guaranteed. The studded contact surface produces a very good exposed concrete surface. The concrete can also be supplied in other colors on request.

## Kapo with studs

| Article description | Title of variant                                                   | Length mm | Concrete cover mm | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/100 pieces | Packaging piece/gibo |
|---------------------|--------------------------------------------------------------------|-----------|-------------------|---------------------------------------------------------------------------|----------------------|----------------------|
| 22118300            | Kapo 25/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 30        | 25                | 500 pieces/bag                                                            | 3,600                | 10.000               |
| 22119300            | Kapo 30/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 30        | 30                | 500 pieces/bag                                                            | 4,200                | 10.000               |
| 22120300            | Kapo 35/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 30        | 35                | 500 pieces/bag                                                            | 5,100                | 10.000               |
| 22121300            | Kapo 40/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 35        | 40                | 250 pieces/bag                                                            | 6,800                | 5.000                |
| 22122300            | Kapo 45/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 35        | 45                | 250 pieces/bag                                                            | 8,100                | 5.000                |
| 22123300            | Kapo 50/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 40        | 50                | 200 pieces/bag                                                            | 10,500               | 4.000                |
| 22124300            | Kapo 55/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 40        | 55                | 175 pieces/bag                                                            | 12,200               | 3.500                |
| 22125300            | Kapo 60/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 40        | 60                | 150 pieces/bag                                                            | 14,400               | 3.000                |
| 22126300            | Kapo 65/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 50        | 65                | 125 pieces/bag                                                            | 17                   | 2.500                |
| 22127300            | Kapo 70/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm) | 50        | 70                | 100 pieces/bag                                                            | 19,700               | 2.000                |