



## Roka-Q acid-resistant



Roka-Q with transverse groove is mounted on the horizontal reinforcing steel. The two spring steel clamps Ø 2 mm are placed over the vertical reinforcing steel and clamp the Roka optimally to the reinforcing steel. Quick installation is guaranteed. The bevel is used to guide the reinforcement cage into the formwork. This prevents the formwork from catching on the spacer. The groove width and depth are produced as required.



| Article description | Title of variant                           | Length mm | Concrete cover mm | Weight kg/100 pieces | Packaging piece/gibo |
|---------------------|--------------------------------------------|-----------|-------------------|----------------------|----------------------|
| 22242400            | Roka-Q with cross groove 25 acid-resistant | 30        | 25                | 7,900                | 8.000                |
| 22243400            | Roka-Q with cross groove 30 acid-resistant | 30        | 30                | 9                    | 7.000                |
| 22244400            | Roka-Q with cross groove 35 acid-resistant | 30        | 35                | 11,500               | 6.000                |
| 22245400            | Roka-Q with cross groove 40 acid-resistant | 30        | 40                | 14                   | 5.000                |
| 22246400            | Roka-Q with cross groove 45 acid-resistant | 30        | 45                | 18,900               | 4.500                |
| 22247700            | Roka-Q with cross groove 50 acid-resistant | 30        | 50                | 23,100               | 4.000                |
| 22248400            | Roka-Q with cross groove 60 acid-resistant | 30        | 60                | 27                   | 3.500                |
| 22249400            | Roka-Q with cross groove 70 acid-resistant | 30        | 70                | 30,900               | 3.000                |