


Bipo mD with galvanized wire



The Bipo with wire can be mounted on upright and horizontal reinforcement. The Bipo is manufactured with a flat contact surface as standard and can also be supplied with a trough on request. The Bipo is supplied with an inserted galvanized binding wire.

Bipo mD with galvanized wire

Article description	Title of variant	Concrete cover mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Packaging piece/pallet	Weight kg/100 pieces
22181500	Bipo 25 mD with galvanized wire	25	20	750 pieces/bag	24000	3,200
22182500	Bipo 30 mD with galvanized wire	30	22	500 pieces/bag	16000	3,700
22183500	Bipo 35 mD with galvanized wire	35	22	500 pieces/bag	16000	4,200
22184500	Bipo 40 mD with galvanized wire	40	22	500 pieces/bag	16000	5,800
22185500	Bipo 45 mD with galvanized wire	45	22	250 pieces/bag	8000	7,100
22186500	Bipo 50 mD with galvanized wire	50	22	250 pieces/bag	8000	7,800
22187500	Bipo 55 mD with galvanized wire	55	22	250 pieces/bag	8000	8,700
22188500	Bipo 60 mD with galvanized wire	60	24	200 pieces/bag	6400	9,800
22180500	Bipo 65 mD with galvanized wire	65	24	200 pieces/bag	6400	10,300
22181150	Bipo 70 mD with galvanized wire	70	24	175 pieces/bag	5600	11
22187350	Bipo 75 mD with galvanized wire	75	24	175 pieces/bag	5600	11,800
22188250	Bipo 80 mD with galvanized wire	80	24	150 pieces/bag	4800	12,200