


## Dreika K1 S with one clamp, bevel cut



The Dreika K1 S is used for vertical reinforcement. S stands for diagonal cut. Two parallel diagonal cuts are made at the factory. This prevents the formwork from touching down and catching. The formwork slides over the slope along the triangular section. The length of the Dreika is designed for a rebar spacing of up to max. 15 cm. A steel clamp Ø2 mm is fitted at the factory. The Dreika can be mounted on reinforcing steel Ø 6-14 mm. The clamp ensures very quick installation. Thanks to its fastening and elongated shape, the Dreika is tilt-proof and stable.

## Dreika K1 S with one clamp, bevel cut

Article description	Title of variant	Concrete cover mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22210200	Dreika 20/18 K1 S with one clamp for Ø6-14 mm, bevel cut	20	180	180 pieces/bag	11	8.000
22211500	Dreika 25/18 K1 S with one clamp for Ø6-14 mm, bevel cut	25	180	175 pieces/bag	13	7.500
22212200	Dreika 30/18 K1 S with one clamp for Ø6-14 mm, bevel cut	30	180	150 pieces/bag	18	5.000
22213600	Dreika 35/18 K1 S with one clamp for Ø6-14 mm, bevel cut	35	180	125 pieces/bag	23	4.000
22214200	Dreika 40/18 K1 S with one clamp for Ø6-14 mm, bevel cut	40	180	100 pieces/bag	24	3.500
22215200	Dreika 45/18 K1 S with one clamp for Ø6-14 mm, bevel cut	45	180	75 pieces/bag	27	2.500
22216200	Dreika 50/18 K1 S with one clamp for Ø6-14 mm, bevel cut	50	180	70 pieces/bag	30	2.000
22217200	Dreika 55/18 K1 S with one clamp for Ø6-14 mm, bevel cut	55	180	65 pieces/bag	33	1.500
22218200	Dreika 60/18 K1 S with one clamp for Ø6-14 mm, bevel cut	60	180	60 pieces/bag	37	1.250
22219200	Dreika 70/18 K1 S with one clamp for Ø6-14 mm, bevel cut	70	180	55 pieces/bag	40	1.100
22231200	Dreika 80/18 K1 S with one clamp for Ø6-14 mm, bevel cut	80	180	50 pieces/bag	44	1.000