


Clipo for Ø6-10 mm



The Clipo /10 is clipped onto standing reinforcement. The plastic clip can be clipped onto reinforcing steel Ø 6-10 mm. Quick installation is guaranteed. The Clipo is the ideal spacer when, for example, the reinforcement cage is embedded in the formwork (e.g. diaphragm walls) or when the formwork is slid over the reinforcement cage (column formwork, cardboard formwork tubes or concrete pipes and shaft structures). The Clipo can also be supplied with two clamps mounted on both sides as an option. The minimum width of the Clipo is then 50 mm (wider widths are also available on request).

Clipo for Ø6-10 mm

Article description	Title of variant	Concrete cover mm	Width B mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22144000	Clipo 20/10 for Ø 6-10 mm	20	52	25	375 pieces/carton	10	7.800
22145000	Clipo 25/10 for Ø 6-10 mm	25	62	25	240 pieces/carton	13,600	5.500
22146000	Clipo 30/10 for Ø 6-10 mm	30	72	25	200 pieces/carton	17,500	4.500
22147000	Clipo 35/10 for Ø 6-10 mm	35	82	25	135 pieces/carton	21	3.500
22148000	Clipo 40/10 for Ø 6-10 mm	40	92	25	114 pieces/carton	26	2.900
22149000	Clipo 45/10 for Ø 6-10 mm	45	102	25	92 pieces/carton	34,700	2.300
22150000	Clipo 50/10 for Ø 6-10 mm	50	112	25	78 pieces/carton	46,900	2.000
22151000	Clipo 55/10 for Ø 6-10 mm	55	122	25	72 pieces/carton	54	1.600
22152000	Clipo 60/10 for Ø 6-10 mm	60	132	25	57 pieces/carton	59,300	1.400
22153000	Clipo 70/10 for Ø 6-10 mm	70	152	25	46 pieces/carton	74,100	1.000
22154200	Surcharge 2 staples Clipo /10 (min. Clipo cutting length = 50 mm)						