


Boomerang L=25 without knobs



The boomerang is a surface spacer and is used with horizontal reinforcement. The contact surface is not studded and should therefore be used in subordinate components without high exposed concrete requirements. The 25 cm length is suitable for use with Q reinforcing steel mesh with a mesh size of 15x15 cm. Due to the bend, the boomerang is stable in position and does not tip over.

Article description	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22269000	Boomerang 20/25, L = 25 cm without knobs	20	17	250	5400	13,030
22269200	Boomerang 25/25, L = 25 cm without knobs	25	17	250	5400	13,700
22270100	Boomerang 30/25, L = 25 cm without knobs	30	19	250	4750	15
22271100	Boomerang 35/25, L = 25 cm without pimples	35	19	250	3600	24
22272100	Boomerang 40/25, L = 25 cm without knobs	40	25	250	2750	25
22273100	Boomerang 45/25, L = 25 cm without knobs	45	25	250	2500	27,300
22274100	Boomerang 50/25, L = 25 cm without pimples	50	25	250	1800	30
22275100	Boomerang 55/25, L = 25 cm without knobs	55	25	250	1600	43
22276100	Boomerang 60/25, L = 25 cm without pimples	60	25	250	1350	55