


Boomerang L=25 with pimples



The boomerang is a surface spacer and is used with horizontal reinforcement. The contact surface is studded and is very suitable for components with exposed concrete requirements. The 25 cm length is used with Q reinforcing steel meshes with a mesh size of 15x15 cm. Due to the bend, the boomerang is stable in position and does not tip over.

Article description	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22269100	Boomerang 20/25 N, L = 25 cm with pimples	20	17	250	5400	13,030
22269000	Boomerang 25/25 N, L = 25 cm with pimples	25	17	250	5400	13,700
22270000	30/25 N boomerang, L = 25 cm mit Noppen	30	19	250	4750	15
22271000	Boomerang 35/25 N, L = 25 cm with pimples	35	19	250	3600	24
22272000	40/25 N boomerang, L = 25 cm mit Noppen	40	25	250	2750	25
22273000	Boomerang 45/25 N, L = 25 cm with pimples	45	25	250	2500	27,300
22274000	Boomerang 50/25 N, L = 25 cm with pimples	50	25	250	1800	30
22275000	Boomerang 55/25 N, L = 25 cm with pimples	55	25	250	1600	43
22276000	Boomerang 60/25 N, L = 25 cm with pimples	60	25	250	1350	55