


## Boomerang L=33 without pimples



The boomerang is a surface spacer and is used with horizontal reinforcement. The contact surface is not studded and should therefore be used in subordinate components without high exposed concrete requirements. The 33 cm length is suitable for use with R reinforcing steel mesh with a mesh size of 15x25 cm. Due to the bend, the boomerang is stable in position and does not tip over.

| Article description | Title of variant                           | Concrete cover mm | a mm | L mm | Packaging piece/pallet | Weight kg/100 pieces |
|---------------------|--------------------------------------------|-------------------|------|------|------------------------|----------------------|
| 22283200            | Boomerang 20/33, L = 33 cm without pimples | 20                | 17   | 330  | 4000                   | 17,200               |
| 22283300            | Boomerang 25/33, L = 33 cm without pimples | 25                | 17   | 330  | 3800                   | 18,100               |
| 22284100            | Boomerang 30/33, L = 33 cm without pimples | 30                | 19   | 330  | 3500                   | 19,800               |
| 22285100            | Boomerang 35/33, L = 33 cm without pimples | 35                | 19   | 330  | 3200                   | 31,700               |
| 22286100            | Boomerang 40/33, L = 33 cm without pimples | 40                | 25   | 330  | 1750                   | 33                   |
| 22287100            | Boomerang 45/33, L = 33 cm without pimples | 45                | 25   | 330  | 1500                   | 36                   |
| 22288100            | Boomerang 50/33, L = 33 cm without pimples | 50                | 25   | 330  | 1500                   | 39,600               |
| 22289100            | Boomerang 55/33, L = 33 cm without knobs   | 55                | 25   | 330  | 1250                   | 56,800               |
| 22290100            | Boomerang 60/33, L = 33 cm without pimples | 60                | 25   | 330  | 1100                   | 66                   |