


## Square profile



The square profile is a surface spacer and is used in the area of floor slabs with horizontal reinforcement. The wide contact surface is suitable for transferring loads over a large area into the substrate. The square profile is very stable and can withstand very high loads. It is suitable for use with heavy reinforcement and where very high traffic loads occur. Quick installation is guaranteed. It is possible to produce the square profiles in short pieces in accordance with the DBV spacer leaflet ( $L < 350$  mm).

Article description	Title of variant	Concrete cover mm	L mm	Packaging metre/pallet	Weight kg/metre
22379000	Square 20, L = 120 cm	20	1.200	2.499,600	0,800
22380000	Square 25, L = 120 cm	25	1.200	1.599,600	1,250
22381000	Square 30, L = 120 cm	30	1.200	1.111,200	1,800
22382000	Square 35, L = 120 cm	35	1.200	816	2,500
22383000	Square 40, L = 120 cm	40	1.200	655,200	3,100
22384000	Square 45, L = 120 cm	45	1.200	488,400	4,100
22385000	Square 50, L = 120 cm	50	1.200	399,600	5
22387100	Square 55, L = 120 cm	55	1.200	327,600	6,100
22386000	Square 60, L = 120 cm	60	1.200	277,200	7,600
22387000	Square 70, L = 120 cm	70	1.200	204	9,800
22388000	Square 80, L = 120 cm	80	1.200	156	12,800
22389000	Square 90, L = 120 cm	90	1.200	123,600	16,300
22390000	Square 100, L = 120 cm	100	1.200	100,800	20