

## 2-component adhesive can



Epoxy resin adhesive. For making waterproof resilient joints with fibrous concrete and fair-faced concrete plugs.

The components are colour-coded: component A is white component B is black

Mixing ratio 1:1

Test report as recommended by German KTW

### Processing

Mixing time: until the adhesive is free from streaks

The surfaces being joined must be free from dust and grease

Pot life: 2 - 2.5 hours at +20°C, min. working temperature 8°C

Reaction temperature: 50-60°C

1 kg of adhesive is sufficient for approx. 40 concrete plugs MKK® B 15

1 kg of adhesive is sufficient for approx. 150 fibrous concrete plugs FB 22/50 mm

| Article description | Title of variant     | Packaging piece/ metre/ metre<br>by the metre/ bucket/ bag/<br>bundle/ box/ can | Weight kg/Component<br>A+B |
|---------------------|----------------------|---------------------------------------------------------------------------------|----------------------------|
| 61800200            | 2-Component adhesive | 1 can each                                                                      | 2 x 1,500                  |
| 61800200            | 2-Component adhesive | 1 can each                                                                      | 2 x 1,500                  |
| 61800200            | 2-Component adhesive | 1 can each                                                                      | 2 x 1,500                  |
| 61800200            | 2-Component adhesive | 1 can each                                                                      | 2 x 1,500                  |