


COMAX[®] X - standard types, shear force parallel to the joint

Shear force applied parallel to lift joint
Formulas and tables



Applications, features, properties and benefits

Benefits:

Standard length 1.25 m

Toothing in transverse direction for optimal force transmission

COMAX[®] L for exposure to longitudinal shear forces parallel to the joint

Significant advantages for planners:

acc. to DIN 1045-1 the COMAX[®] L is classed as "TOOTHED"

Dimensionally stable cover facilitates short striking times

Special types (except K and BK) available on request

Technical data

Agenda:

B = Typ/Blechbreite/Elementbreite

l = Verankerungslänge

b = Bügelbreite

h = Bügelhöhe

e = Bügelabstand

COMAX® X - standard types, shear force parallel to the joint

Article description	BSt Ø mm	Bracket spacing e in cm	b1 cm	h cm	l cm	Packaging piece/pallet	Weight kg/piece	Weight kg/Component A+B
52110815	8	15	8	15	32	80 Stück/Palette = 96 m		
52241220	12	20	15	21	46	48 Stück/Palette	8,990	test
52110820	8	20	8	15	32	80 pieces/pallet		
54111015	10	15	8	15	39	80 pieces/pallet		
52111020	10	20	8	15	39	80 pieces/pallet		
52140815	8	15	11	15	32	80 pieces/pallet = 100m		
52140820	8	20	11	15	32	80 pieces/pallet		
52141010	10	10	11	15	39	108 Stück/Palette		
52141015	10	15	11	15	39	80 pieces/pallet		
52141020	10	20	11	15	39	80 pieces/pallet		
52141215	12	15	11	15	46	80 pieces/pallet		
52141220	12	20	11	15	46	80 pieces/pallet		
52160815	8	15	13	15	32	60 pieces/pallet = 75m		
52160820	8	20	13	15	32	60 pieces/pallet		
52161010	10	10	13	15	39	84 Stück/Palette		
52161015	10	15	13	15	39	60 pieces/pallet		
52161020	10	20	13	15	39	60 pieces/pallet		
52161215	12	15	13	15	46	60 pieces/pallet		
52161220	12	20	13	15	46	60 pieces/pallet		
52190815	8	15	16	15	32	60 pieces/pallet = 75m		
52190820	8	20	16	15	32	60 pieces/pallet		
52191010	10	10	16	15	39	72 Stück/Palette		
52191015	10	15	16	15	39	60 pieces/pallet		
52191020	10	20	16	15	39	60 pieces/pallet		
52191215	12	15	16	15	46	60 pieces/pallet		
52191220	12	20	16	15	46	60 pieces/pallet		
52220815	8	15	19	15	32	48 pieces/pallet = 60m		
52220820	8	20	19	15	32	48 pieces/pallet		
52221010	10	10	19	15	39	48 Stück/Palette		
52221015	10	15	19	15	39	48 pieces/pallet		
52221020	10	20	19	15	39	48 pieces/pallet		
52221215	12	15	19	15	46	48 pieces/pallet		
52221220	12	20	19	15	46	48 pieces/pallet		

COMAX® X - standard types, shear force parallel to the joint

Article description	BSt Ø mm	Bracket spacing e in cm	b1 cm	h cm	l cm	Packaging piece/pallet	Weight kg/piece	Weight kg/Component A+B
52240815	8	15	21	15	32	40 pieces/pallet = 50m		
52240820	8	20	21	15	32	40 pieces/pallet		
52241010	10	10	21	15	39	48 Stück/Palette		
52241015	10	15	21	15	39	40 pieces/pallet		
52241210	12	10	21	15	32	40 pieces/pallet		
52241215	12	15	21	15	46	40 pieces/pallet		