


## GripTec GTB positioning joint I



Positioning coupling GripTec GTB-P I / P I repair for straight and bent, not free-rotating and / or longitudinally fixed rebars (PI).

### Technical data

Minimum distance according DIN 1045-1 1 ds / min. 2 cm

\* Thread pitch does not correspond to standard pitch.

| Article description | Thread    | Ø mm | BSt Ø mm | a mm | b mm   | L mm    | SW mm | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/piece |
|---------------------|-----------|------|----------|------|--------|---------|-------|---------------------------------------------------------------------------|-----------------|
| 32121430            | M 14x2,0  | 20   | 12       | 70   | 26     | 121,200 | 22    | 1 piece                                                                   | 0,200           |
| 32141630            | M 16x2,0  | 24   | 14       | 85   | 30     | 143,800 | 24    | 1 piece                                                                   | 0,240           |
| 32161830            | M 18x2,5  | 26   | 16       | 100  | 34     | 165,400 | 27    | 1 piece                                                                   | 0,300           |
| 32202230            | M 22x2,5  | 34   | 20       | 115  | 42     | 195,600 | 32    | 1 piece                                                                   | 0,620           |
| 32252730            | M 27x3,0  | 40   | 25       | 120  | 46,500 | 213,600 | 41    | 1 piece                                                                   | 1               |
| 32283030            | M 30x2,5* | 45   | 28       | 105  | 52     | 199     | 46    | 1 piece                                                                   | 1,480           |
| 32323330            | M 33x3,5  | 50   | 32       | 140  | 58,500 | 245,500 | 50    | 1 piece                                                                   | 2,060           |